

GORI 88 COMPACT

Translucent Wood Stain



GORI 88 Compact Translucent Wood Stain is a solvent based, non-drip, durable, semi-transparent wood stain for protecting and decorating exterior wood. Containing innovative Slow Release technology, the active ingredients are only released when necessary ensuring a long-lasting quality finish. Ideal for use on windows, doors and cladding



KEY PROPERTIES

- ▶ For windows, doors and cladding
- ▶ With Slow Release technology for longer protection
- ▶ Durable, semi-transparent, non-drip. Protects against UV-rays, fungi and mould

PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material. To obtain maximum performance from this product, old paint and varnish should be completely removed. Treat fungal or algal growth with a Sterilisation Wash as directed. Treat bare timber surfaces with an GORI 11 Wood Preservative as directed. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during preparations of pre-1960s paint surfaces over wood and metal as they may contain harmful lead. Paint colours will differ from wet to dry. For more information on our products and service please call 01924 354354.

APPLICATION

Ensure maximum ventilation during application and drying. Easy to apply by brush or roller. Stir lightly before use. Do not thin.

Do not apply when moisture of the wood is above 18% at the time of treatment or if the temperature is below +5°C and relative humidity is below 80%. Avoid application in damp conditions or externally when rain is imminent. Never apply wood protection in direct sunlight.

Apply one coat of GORI 11 Wood Preservative* as directed before applying two coats of GORI 88 Compact Translucent Wood Stain.

Please note that the final colour result depends on the colour of the substrate. If more than one can of the same colour is to be used in the same area, intermix before use. Additional coats may be required in certain colours or when attempting a wide colour change.

*GORI 11 Wood Preservative is not available in ROI.

COVERAGE

GORI 88 Compact Durable Wood Stain will cover approximately 10-12m²/l depending on the substrate. Do not apply wood protection in direct sunlight.

DRYING TIME

Recoatable after 24 hours - at 23°C and standard humidity of 60%.

CLEANER

White Spirit

COLOUR RANGE

Available in a tintable colour range.

SIZE

Available in 0.75L, 2.5L & 5L

AFTER USE

Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use in soapy water and rinse thoroughly. Do not empty product into drains or water courses. Some local authorities have special facilities for the disposal of waste coatings.

STORAGE

STORE AWAY FROM HEAT AND FLAME

Keep container tightly closed. To avoid the risk of spillage, always store and transport in a secure upright position.

EU limit value for this product (Cat A/e): 400g/l (2010).

This product contains max 400g/l VOC.

SAFE USE INFORMATION

Keep out of reach of children.

Avoid contact with skin and eyes.

Do not ingest.

Do not breathe spray. Wear respiratory protection.

If medical advice is needed have container or label to hand.

Please refer to Product label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/transport/storage/disposal/emergency.

SDS available by calling 01924 354 354.

