

# GORI 05 EXPRESS

## Decking Oil



**GORI 05 Express Decking Oil** is a durable, water based, water repellent coating for exterior decking areas. Use on all types of wood to help prevent cracks, drying and decay. Once treated, the surface of the wood becomes water repellent and is protected against moisture and weathering. GORI 05 Express Decking Oil offers increased durability compared to conventional decking oils.



### KEY PROPERTIES

- ▶ For exterior wooden decking and stairs
- ▶ Quick dry - suitable for use 1 hour after application\*
- ▶ Helps prevent cracks, drying and decay

### PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material. To obtain maximum performance from this product, old paint and varnish should be completely removed. Treat fungal or algal growth with a Sterilisation Wash as directed. Treat bare timber surfaces with an GORI 11 Wood Preservative\*\* as directed. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during preparations of pre-1960s paint surfaces over wood and metal as they may contain harmful lead. Paint colours will differ from wet to dry. For more information on our products and service please call 01924 354354.

\*\*GORI 11 Wood Preservative is not available in the Republic of Ireland.

### APPLICATION

Ensure good ventilation during application and drying.  
Easy to apply by brush or roller. Stir well.

Do not apply when moisture of the wood is above 18% at the time of treatment or if the temperature is below +5°C and relative humidity is below 80%. Avoid application in damp conditions or externally when rain is imminent.

Apply one coat of GORI 11 Wood Preservative\*\* as directed before applying two coats of GORI 05 Express Decking Oil. For the first coat, apply a thin layer along the wood grain, two decking boards at a time in order to obtain an even result. Wipe off surplus oil after 5-10 minutes with a lint free cloth. After the first coat the wood grain may rise. If that is the case, you can sand the deck lightly after 1-2 hours. Apply the second coat as the first. Apply a maintenance treatment every 1-2 years to obtain optimum protection. Treat extremely exposed areas regularly. Please note that the final colour result depends on the colour of the substrate.

### COVERAGE

GORI 05 Express Decking Oil will cover approximately 15 sqm/l.

### DRYING TIME

Touch dry, recoatable and walkable: after 1 hour  
\*(at 23°C and a standard humidity of 60%).

### CLEANER

Clean Water

### COLOUR RANGE

Available in Clear, Teak, Oak & Walnut

### SIZE

Available in 2.5L

### AFTER USE

Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use in soapy water and rinse thoroughly. Do not empty product into drains or water courses. Some local authorities have special facilities for the disposal of waste coatings.

### STORAGE

PROTECT FROM FROST

Keep container tightly closed. To avoid the risk of spillage, always store and transport in a secure upright position. As wood is an organic material, there is no guarantee that the same wood species will react the same way in different areas, when treated/coated/stained.

EU limit value for this product (Cat A/f): 130g/l (2010).  
This product contains max 50g/l VOC.

### SAFE USE INFORMATION

Keep out of reach of children.

Avoid contact with skin and eyes.

Do not ingest.

Do not breathe spray. Wear respiratory protection.

If medical advice is needed have container or label to hand.

Please refer to Product label & Safety Data Sheet (SDS) for full hazard classification and information on safe handling/use/transport/storage/disposal/emergency action.

SDS available by calling 01924 354 354.



DATE OF ISSUE: 15.01.2021  
VERSION: 1  
PRODUCT EMG: 10130RUK13X05

**GORI**<sup>®</sup>  
Professional